



Automatic air valves, with double orifice and integrated valve, flanged PN 16, 25



Art. 706-712

Flanges: UNI EN 1092-2 PN 16-25 Installation: at the high part of pipelines APPLICATIONS • Aqueducts • Irrigation plants

Fig. 706: flanges drilling PN 16Fig 712: Flanges drilling PN 25

Epoxy paiting suitable for drinking water applications.

The double orifice automatic air valves with integrated valve are used for applications related to troubles with air in the pipelines. The double air valves with integrated valve working as isolating valve allow maintenance or replacement of balls in line. The minimum pressure on seat is 0,3 bar.

The double ball air valves have three functions:

- Discharge large amount of air during filling operations
- Discharge small amount of air during working operations
- Let air in during piping emptying operations

		Materials
ductile iron GGG40/50, EN-GJS-400/500	body	
ductile iron GGG40/50, EN-GJS-400/500	cover	
ABS / NBR / st.st. AISI 304	floating balls	
EPDM	gasket	
ероху	painting	

Dimensions	DN	L mm.	H mm.	D mm.	Weight kg.
	50	290	415	165	22
	65	290	415	185	30
	80	290	425	200	30
	100	530	480	220	52
	150	656	515	285	109
L D	200	790	615	340	196

Pressure	DN	Nominal pressure	Test pressure Mpa		Max working pressure Mpa
	mm	BAR	body	seat	40°C
	50-200	16	2,4	1,76	1,6
	50-200	25	4,0	2,75	2,5

DN of pipeline	DN of air valve
< 200 mm	DN 50
200 mm - 250 mm	DN 80
300 mm - 500 mm	DN 100
600 mm - 900 mm	DN 150
1000 mm - 1200 mm	DN 200
> 1200 mm	DN 250 o 2 x DN 200